

PRINTABLE METALLIZED VINYL WITH AIR EGRESS TECHNOLOGY

PHYSICAL SPECIFICATIONS

Adhesive	Removable Acrylic PSA (1.0 mil/25 µm)
Color	Fine Brush Silver, Matte Silver, Smooth Silver, Smooth Gold
Caliper <i>facestock</i>	3.0 mil. (75 µm)
Caliper <i>facestock + adhesive</i>	4.0 mil. (100 µm)
Release Liner	Poly-coated embossed air-egress technology (162 gsm)
Adhesion to Steel*	20-30 oz/in 27N/100mm (24 oz.)
Durability	Intended for indoor applications only (6 months)
Shelf Life**	1 year
Temperature Limit (F)	-30F to 140F
Temperature Limit (C)	-34C to 60C
Availability	54"x10 yd. (137 cm. x 9.14 m.) 54"x50 yd. (137 cm. x 45.7 m.)

APPLICATIONS

- Point of purchase displays
- Posters
- Counter mats
- Window graphics
- Trade show displays and graphics

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

FEATURES

- Printable - solvent, ecosolvent, latex, UV curable and screen printing platforms
- Excellent lay-flat characteristics and stability during cutting and weeding
- Deep embossed vinyl facestock
- New air egress technology
- Proprietary, and more forgiving, removable adhesive
- Compatible with liquid and film laminates

APPLICATION INFORMATION

- Flat or simple curved surfaces
- Minimum application temperature = 50F (10C)
- Use of a heat gun is not advisable due to potential discoloration

TRANSFER TAPE

Scratching of the film during application can be prevented by using one of our recommended application tapes (4075RLA, 4078RLA).

AVAILABILITY

54"x10 yd. (137 cm. x 9.14 m.)

54"x50 yd. (137 cm. x 45.7 m.)



RTape Corp.

6 Ingersoll Road
South Plainfield, NJ
07080
T 1-800-440-1250
www.rtape.com

RESPONSIVE
RELIABLE
RESOURCEFUL